

SECTION 017329 - CUTTING AND PATCHING

PART 1 GENERAL

1.1 SUBMITTALS

- A. Submit written request in advance of executing cutting or alteration that affects:
 - 1. Work of Developer or separate contractor.
 - 2. Structural integrity of project.
 - 3. Integrity or effectiveness of weather exposed or moisture resistant elements or systems.
 - 4. Efficiency, operational life, maintenance, or safety of operational elements.
 - 5. Visual qualities of sight exposed elements.
- B. Include in Request:
 - 1. Identification of project.
 - 2. Description of work affected.
 - 3. Necessity for cutting or patching.
 - 4. Effect of cutting or patching on work of Developer or separate contractor, or on structural, weatherproof, or visual integrity of project.
 - 5. Description of proposed work:
 - a. Scope of cutting and patching.
 - b. Subcontractor and trades to execute work.
 - c. Products proposed to be used.
 - d. Extent of refinishing.
 - 6. Alternate to cutting and patching.
 - 7. Cost proposal, if applicable.
 - 8. Written permission of any separate contractor whose work will be affected.
- C. If conditions of work or schedule necessitate a change of material from that originally installed, submit substitution request in accordance with Section 012500.

PART 2 PRODUCTS

Not used

PART 3 EXECUTION

3.1 PREPARATION

- A. Examine existing conditions of work, including elements subject to movement or damage during cutting and patching.
- B. After uncovering work, examine conditions affecting installation of new products or performance of work.
- C. Provide protection for other portions of project.
- D. Provide protection from elements.

3.2 CUTTING AND PATCHING

- A. Execute cutting to include excavating, fitting, and patching of Work required to:
 - 1. Make several parts fit properly.
 - 2. Uncover work to provide for installation of ill timed work.
 - 3. Remove and replace defective work.
 - 4. Remove and replace work not conforming to requirements of Contract Documents.
 - 5. Provide routine penetrations of nonstructural surfaces for installation of piping and electrical conduit.

- B. Execute fitting and adjustment of products to provide finished installation to comply with specified tolerances, and finishes.
- C. Execute cutting and demolition by methods that will prevent damage to other work, and will provide proper surfaces to receive installation of repairs and new work.
- D. Execute excavating and backfilling by methods that will prevent damage to other Work, and will prevent settlement.
- E. Employ original installer or fabricator to perform cutting and patching for:
 - 1. Weather exposed or moisture resistant elements.
 - 2. Sight exposed finished surfaces.
- F. Restore work that has been cut or removed; install new products to provide completed Work in accordance with requirements of Contract Documents.
- G. Refinish entire surfaces as necessary to provide an even finish:
 - 1. Continuous surfaces: To nearest intersections.
 - 2. Assembly: Refinish entirely.

END OF SECTION