

SECTION 015800 - PROJECT IDENTIFICATION

PART 1 GENERAL

1.1 QUALITY ASSURANCE

- A. Project Sign:
 - 1. Design sign and structure to withstand 50 MPH wind velocity.
 - 2. Sign Painter: Experienced as a professional sign painter for minimum 3 years.
 - 3. Finishes and painting: Adequate to withstand weathering, fading, and chipping for duration of construction.

- B. Do not erect other signs at site without Developer's approval, except those required by governing authorities.

1.2 SUBMITTALS

- A. Submittals for Review:
 - 1. Shop Drawings: Show content, layout, lettering, colors, structure, sizes, and grades of members.
 - 2. Samples: 3 x 3 inch samples of each paint color.

PART 2 PRODUCTS

2.1 MATERIALS

- A. Structure and Framing: New lumber, structurally adequate.
- B. Sign Surfaces: Exterior grade plywood with medium density overlay, nominally 3/4 inch thick, standard large sizes to minimize joints.
- C. Rough Hardware: Galvanized steel or aluminum.
- D. Paints: Alkyd type, exterior quality, semigloss sheen.

2.2 FABRICATION

- A. Provide one sign of following design:
 - 1. Area: 32 square feet.
 - 2. Bottom edge of sign: 6 feet above ground.
 - 3. Content:
 - a. Project title.
 - b. Names and titles of:
 - 1) Developer.
 - 2) Landscape Architect.
 - 3) Contractor.
 - 4. Graphic design, colors, and lettering style: As designated by Landscape Architect.

PART 3 EXECUTION

3.1 INSTALLATION

- A. Install project identification sign within 30 days after date of Notice to Proceed.
- B. Erect at designated location.
- C. Erect supports and framing on secure foundation, rigidly braced and framed to resist wind loadings.
- D. Install sign surface plumb and level, with butt joints. Anchor securely.

E. Paint exposed surfaces of sign, supports, and framing.

3.2 MAINTENANCE

A. Maintain signs and supports clean. Repair deterioration and damage.

3.3 REMOVAL

A. Remove signs, framing, supports, and foundations at completion of Project and restore the area.

END OF SECTION